

1-Way Cassette Type GMV5 Unit – Technical Specifications

MODEL		GMV-ND22TD/A-T	GMV-ND28T/A-T	GMV-ND36T/A-T	GMV-ND45T/A-T	GMV-ND50T/A-T					
Capacity	kW	2,20	2,50	2,80	3,20	3,60	4,00	4,50	5,00	5,00	5,60
Capacity	Btu/h	7.506	8.53	9.554	10.918	12.283	13.648	15.354	17.06	17.06	19.107
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	600/500/450		600/500/450		600/500/450		830/600/500		830/600/500	
Sound Pressure Level	dB(A)	36/32/28		36/32/28		36/32/28		40/35/30		40/35/30	
Diameter Liquid-Gas	inch	1/4" – 3/8"		1/4" – 3/8"		1/4" – 1/2"		1/4" – 1/2"		1/4" – 1/2"	
Unit Dimension LxHxD/ Weight	mm/kg	1200x460x55 / 4,2		1200x460x55 / 4,2		1200x460x55 / 4,2		1200x460x55 / 4,2		1200x460x55 / 4,2	