

Floor Ceiling Indoor Units – Technical Specifications

INDOOR FLOOR CEILING UNITS		GTH(09)BA-K3DNA1A/I		GTH(12)BA-K3DNA1A/I		GTH(18)BA-K3DNA1A/I		GTH(24)BB-K3DNA2A/I	
Operation		Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Capacity	kW	2.52	2.81	3.52	3.84	5.01	5.51	7.12	8
Capacity	Btu	8,600	9,600	12,000	13,100	17,100	18,800	24,300	27,300
Power Input	W	55	55	55	55	110	110	110	110
Power supply	V-Ph-Hz	230V ~ 1N – 50 Hz							
Power supply cable IDU / Com.	mm ²	NO/ 4×1,5		NO/ 4×1,5		NO/ 4×1,5		NO/ 4×1,5	
Air Flow Volume	m ³ /h	650		650		950		1400	
Indoor Unit Sound Pressure Level (H/M/L)	dB(A)	40/36		40/36		45/40		48/40	
Diameter Liquid-Gas Connection Pipe	inch	1/4" – 3/8"		1/4" – 3/8"		1/4" – 1/2"		3/8" – 5/8"	
Diameter Condensing Pipe	mm	Φ16		Φ16		Φ16		Φ16	
Indoor Unit Dimension LxHxD /Weight	mm/kg	1220 x 700 x 225 / 40		1220 x 700 x 225 / 40		1220 x 700 x 225 / 40		1220 x 700 x 225 / 45	