

Super Slim Free Match Duct type indoor units Ecodesign – Technical Specifications

MODEL		GFH(09)EA-K3DNA1A/I		GFH(12)EA-K3DNA1A/I		GFH(18)EA-K3DNA1A/I		GFH(21)EA-K3DNA1A/I		GFH(24)EA-K3DNA1A/I	
Operation		Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Capacity	kW	2,52	2,81	3,52	3,87	5,01	5,51	6,01	6,62	7,12	8,00
Capacity	Btu	8.6	9.6	12	13.2	17.1	18.8	20.5	22.6	24.3	27.3
Power Input	W	75	75	65	65	80	80	110	110	110	110
Power Supply	V-Ph-Hz	230V ~ 1N – 50 Hz									
Power Supply Cable IDU / Com.	mm ²	NO / 4x1,5		NO / 4x1,5		NO/ 4x1,5		NO / 4x1,5		NO / 4x1,5	
Air Flow Volume	m ³ /h	450		500		700		1000		1000	
Indoor Unit Sound Pressure Level (H/M/L)	dB(A)	37/31		39/32		40/33		42/34		42/34	
Diameter Liquid-Gas Connection Pipe	inch	1/4" – 3/8"		1/4" – 3/8"		1/4" – 1/2"		3/8" – 5/8"		3/8" – 5/8"	
Diameter Condensing Pipe	mm	Φ20		Φ20		Φ20		Φ20		Φ20	
Indoor Unit Dimension LxHxD /Weight	mm/kg	700 x 615 x 200 / 22		700 x 615 x 200 / 23		900 x 615 x 200 / 27		1100 x 615 x 200 / 31		1100 x 615 x 200 / 31	