

Console GMV5 – Technical Specifications

MODEL		GMV-ND22C/A-T		GMV-ND28C/A-T		GMV-ND36C/A-T		GMV-ND45C/A-T		GMV-ND50C/A-T	
Capacity	kW	2,20	2,50	2,80	3,20	3,60	4,00	4,50	5,00	5,00	5,60
Capacity	Btu/h	7.506	8.53	9.554	10.918	12.283	13.648	15.354	17.06	17.06	19.107
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	400/320/270		400/320/270		480/400/300		680/600/500		680/600/500	
Sound Pressure Level	dB(A)	38/33/27		38/33/27		40/37/32		46/43/39		46/43/39	
Diameter Liquid-Gas	inch	1/4" – 3/8"		1/4" – 3/8"		1/4" – 3/8"		1/4" – 1/2"		1/4" – 1/2"	
Unit Dimension LxHxD/ Weight	mm/kg	700x215x600 / 16		700x215x600 / 16		700x215x600 / 16		700x215x600 / 16		700x215x600 / 16	