

Slim GMV5 – Technical Specifications

Model		GMV-H224WL/A-X		GMV-H280WL/A-X		GMV-H335WL/A-X	
Capacity Range		8 HP		10 HP		12 HP	
Capacity	kW	22,40	24,00	28,00	30,00	33,50	35,00
Capacity	Btu/h	76.429	81.888	95.536	102.36	114.302	119.42
Consumption	W	7,20	6,50	9,80	8,80	10,80	10,20
Power Input	A	12,50	11,00	17,50	15,70	19,30	18,20
EER – COP – CLASS	W/W	3,11	3,69	2,86	3,41	3,10	3,43
Ambient Temperature Range	°C	-5~52	-20~27	-5~52	-20~27	-5~52	-20~27
Power Supply	V-Ph-Hz	380-415V ~ 3N – 50 Hz		380-415V ~ 3N – 50 Hz		380-415V ~ 3N – 50 Hz	
Power Connection Cable ODU.-IDU. / Com.	mm ²	5×4		5×4		5×4	
Sound Pressure Level ODU	dB(A)	58	60	59	62	60	63
Air Flow Volume	m ³ /h	8.000 / 2		11.000 / 2		11.000 / 2	
Compressor Type/ Number		Mitsubishi Rotary Inverter/ 1		Hitachi Scroll Inverter/ 1		Hitachi Scroll Inverter/ 1	
Refrigerant Charge		R410 – 5,50kg		R410 – 7,10kg		R410 – 8,00kg	
Diameter Liquid-Gas Connection Pipe	inch	3/8" – 3/4"		3/8" – 7/8"		1/2" – 1 1/8"	
Max IDU's	Units	13		17		20	
Dimension LxHxD /Weight	mm/kg	940×1.430×320/ 133		940×1.615×460/ 166		940×1.615×460/ 177	