

Super Slim GMV5 Duct Type Units – Technical Specifications

Model		GMV-ND22PL/B-T		GMV-ND28PL/B-T		GMV-ND36PL/B-T		GMV-ND45PL/B-T	
Capacity	kW	2,20	2,50	2,80	3,20	3,60	4,00	4,50	5,00
Capacity	Btu/h	7.506	8.53	9.554	10.918	12.283	13.648	15.354	17.06
Power Supply	V-Ph-Hz	220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz		220-240V ~ 1N – 50 Hz	
Air Flow Volume (H/M/L)	m ³ /h	450/350/250		450/350/250		550/450/350		750/600/450	
Sound Pressure Level	dB(A)	30/28/22		30/28/22		31/28/25		33/31/27	
Available ESP	Pa	15		15		15		15	
Diameter Liquid-Gas Connection Pipe	inch	1/4" – 3/8"		1/4" – 3/8"		1/4" – 1/2"		1/4" – 1/2"	
Unit Dimension LxHxD/ Weight	mm/kg	710x450x200 / 18,5		710x450x200 / 18,5		710x450x200 / 19,5		1010x450x200 / 23,5	