

Water Tank– Technical Specifications T

Water Tank			SXVD200 LCJ/A-K	SXVD300 LCJ/A-K	SXVD200 LCJ2/A-K	SXVD300 LCJ2/A-K	SXVD200 LCJ/A-M	SXVD300 LCJ/A-M	SXVD200 LCJ2/A-M	SXVD300 LCJ2/A-M
Tanks Capacity	Lit		200	300	200	300	200	300	200	300
Max Temperature	°C	20-50°C with heat pump – 50-80°C with Electrical Heaters								
Electrical Heaters	KW		3	3	3	3	3	3	3	3
Power Supply		220 ~ 230 V – 1N – 50Hz				380 ~ 415 V – 3N – 50Hz				
Dimensions (H/D)	mm	1595/Φ540	1620/Φ620	1595/Φ540	1620/Φ620	1595/Φ540	1620/Φ620	1595/Φ540	1620/Φ620	1620/Φ620
Material		Stainless Steel – Polyurethane insulation								
Sanitary Water Connections	in	Female 1/2 " BSP								
Water Connections of Exchanger 1	in	Female 3/4 " BSP								
Water Connections of Exchanger 2	in	/	/	Female 3/4 " BSP		/	/	Female 3/4 " BSP		
Weight	kg	68	82	71	87	68	82	71	87	